
ECHOSORB®

12 & 24



PANELS





KEY BENEFITS

- Can be used in conjunction with our Acoustic fabrics to give a more aesthetic tone to the room
- Environmentally friendly non-toxic, non-irritant, recycled fibres and will not shed
- Long life durability
- Multi-use acoustic wall panel - hang or frame

APPLICATIONS

- Offices ideal for modular office partitioning
- Workstations
- Halls
- Call centres
- Learning spaces
- Retail
- Schools
- Community centres

STANDARD FIRE RATING

25mm: ISO 9705-1993 Classification:

Group 1-S AS ISO 9705 – 2003

Classification: Group 1 EN13501

1:2007+A1:2009: B – s2, d0

50mm: EN13501-1:2007+A1:2009: B - s2, d2

Suitable for indoor use only and has been tested to the following standard:

ASTM 5036: 83

VOC EMISSIONS

VOC concentration: 0.01mg/m3

IMPACT RESISTANCE

Impact resistance tested to EN13964:2004 and meets the criteria of Class 1A; not adversely affected at impact velocities over 16.5m/s

DESCRIPTION

Offering incredible sound absorption for small spaces, Echosorb® acoustic panels offer maximum flexibility and sound control. Echosorb® reduces noise levels by around 50%.



FEATURES

- No frame or facing needed
- Standard product is white however there are 17 fabric colours available option available to print on fabric
- For medium to high frequency sound control
- Easy to install
- Unaffected by water
- Maintenance and care is easy blot spills quickly and wipe with a damp cloth
- Made from 100% Polyester fibre (PET)
- Standard sheet dimension: 1200mm x 2400mm
- Echosorb® 12 is 12mm thick at 2.4kg/m
- Echosorb® 24 is 24mm thick at 3.6kg/m






SCORE AND TEST RESULTS

Frequency (Hz)	125	250	500	1000	2000	4000	NRC
EchoSorb® 12 (No air gap)	0.05	0.10	0.30	0.65	0.90	0.95	0.45
EchoSorb® 12 (with 25mm air gap)	0.05	0.30	0.60	0.95	0.95	0.85	0.70
EchoSorb® 24 (No air gap)	0.05	0.20	0.60	0.90	1.00	1.00	0.70
EchoSorb® 24 (with 25mm air gap)	0.15	0.40	0.85	0.95	0.95	0.95	0.80

Absorption Coefficient for EchoSorb® 12 & 24



- EchoSorb® 12 (No air gap)
 - Test No. T0712-3
- EchoSorb® 12 (with 25mm air gap)Test No. T0712-6
- EchoSorb® 24 (No air gap)
 - Test No. T1961-1
- EchoSorb® 24 (with 25mm air gap)
 - Test No. T1326-2

COLOURS AVAILABLE

